

Chain Slings

Grade 80 Double Leg - Latch Type Hook with shorteners

- Grade 80 Chain with Latch type Sling Hooks
 - 2 x shorteners Grade 80 chain with G80 Shortening Grab Hooks
- Approved Standards AS 3775.1**

Model	Length	Chain Size	WLL 1	WLL 2	WLL @60°	WLL @90°	WLL @120°																																
CS2X08	2	8	2.0	1.5	3.5	2.8	2.0																																
CS2X10	2	10	3.2	2.4	5.5	4.5	3.2																																
CS2X13	2	13	5.3	4.0	9.2	7.5	5.3																																
CS3X08	3	8	2.0	1.5	3.5	2.8	2.0																																
CS3X10	3	10	3.2	2.4	5.5	4.5	3.2																																
CS3X13	3	13	5.3	4.0	9.2	7.5	5.3																																
CS4X08	4	8	2.0	1.5	3.5	2.8	2.0																																
CS4X10	4	10	3.2	2.4	5.5	4.5	3.2 </tr <tr> <td>CS4X13</td> <td>4</td> <td>13</td> <td>5.3</td> <td>4.0</td> <td>9.2</td> <td>7.5</td> <td>5.3</td> </tr> <tr> <td>CS6X08</td> <td>6</td> <td>8</td> <td>2.0</td> <td>1.5</td> <td>3.5</td> <td>2.8</td> <td>2.0</td> </tr> <tr> <td>CS6X10</td> <td>6</td> <td>10</td> <td>3.2</td> <td>2.4</td> <td>5.5</td> <td>4.5</td> <td>3.2</td> </tr> <tr> <td>CS6X13</td> <td>6</td> <td>13</td> <td>5.3</td> <td>4.0</td> <td>9.2</td> <td>7.5</td> <td>5.3</td> </tr>	CS4X13	4	13	5.3	4.0	9.2	7.5	5.3	CS6X08	6	8	2.0	1.5	3.5	2.8	2.0	CS6X10	6	10	3.2	2.4	5.5	4.5	3.2	CS6X13	6	13	5.3	4.0	9.2	7.5	5.3
CS4X13	4	13	5.3	4.0	9.2	7.5	5.3																																
CS6X08	6	8	2.0	1.5	3.5	2.8	2.0																																
CS6X10	6	10	3.2	2.4	5.5	4.5	3.2																																
CS6X13	6	13	5.3	4.0	9.2	7.5	5.3																																

