

## Round Webbing

- Round Slings manufactured to A.S. 4497.1 - 1997 - Safety Factor 7:1
- WLL (Working Load Limit) is clearly marked on each sling
- Each sling is colour coded to WLL for safety (**each stripe is equal to 1 ton capacity**)
- Test Certificate supplied with every sling



### Sizes:

- 1,000kg - 0.5m, 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m & 6m
- 2,000kg - 0.5m, 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m & 6m
- 3,000kg - 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m & 6m
- 4,000kg - 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m & 6m
- 5,000kg - 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m & 6m
- 6,000kg - 3m, 4m & 6m
- 8,000kg - 4m & 6m
- 10,000kg - 4m, 6m, 8m & 10m



Sling Colour/WLL Guide	
1,000kg	5,000kg
2,000kg	6,000kg
3,000kg	8,000kg
4,000kg	10,000kg

## Flat Webbing Slings

- Flat Slings manufactured to A.S. 1353 Parts 1&2 1990 - Safety Factor 8:1
- WLL (Working Load Limit) is clearly marked on each sling
- Each sling is colour coded to WLL for safety
- Test Certificate supplied with every sling

### Sizes:

- 1,000kg - 1m, 2m, 3m, 4m, 5m & 6m
- 2,000kg - 1m, 2m, 3m, 4m, 5m & 6m
- 3,000kg - 1m, 2m, 3m, 4m, 5m & 6m
- 4,000kg - 2m, 3m, 4m, 5m & 6m
- 5,000kg - 2m, 3m, 4m, 5m, 6m & 8m



Scan for Video



## Heavy-duty Ratchet Tie Downs

- Heavy duty Ratchet Tie Down assemblies for securing loads safely with minimum effort
- Complete with straps hooks and keepers
- Comply with AS/NZS 4380.2001

### Sizes:

- 0.75T - 25mm x 5 metre (P/N: GRTD25-0.75T)
- 1.5T - 35mm x 6 metre (P/N: GRTD35-1.5T)
- 2.5T - 50mm x 9 metre (P/N: GRTD50-2.5T)

